



# Bring modularity and flexibility to the world of remote data acquisition

## Data Logger 4G LTE



### Simplicity

The Schneider Electric Data Logger 4G LTE is an ultra-low-power, fully-autonomous wireless telemetry device that operates best-of-class sensors. The sampled sensor data is collected, transmitted securely, and then stored on Schneider Electric's cloud-server or a customer's on-premises server. Data Loggers are remotely configurable, and data can be visualized and managed via Schneider Electric's web-based IIoT Platform. Data can also be integrated into SCADA and other software systems.

### Benefits

- EcoStruxure™ Process Instrumentation's Data Logger 4G LTE offers simplified installation, integrated diagnostics, long battery lifetime, remote communication options, and low overall maintenance for remote location installations.
- Dominant IIoT solution in the infrastructure market for creating cyber-secure, plug-and-play, affordable smart infrastructure networks.

[schneider-electric.com](https://schneider-electric.com)

Life Is On

**Schneider**  
Electric

# Experience the Benefits of the Data Logger 4G LTE



## SCADA & Software

From cloud-based hosting and an intuitive user-interface to secured and streamlined SCADA connectivity, the Data Logger delivers data directly where it is needed. Integrating with models, analytics, and business intelligence solutions has never been easier.



## Autonomous Operation & Redundant Communication

Low-power and predictive analysis algorithms result in up to 30% extended battery life. Redundant communication concurrently supports LTE (4G), 3G, 2G, LPWAN and Bluetooth connectivity.



## Rugged Design

Molded polycarbonate enclosure with IP 68 / NEMA 6P waterproofing rating allows for installation in the most corrosive and aggressive of environments, in both industrial and commercial applications.



## Cyber-Security & Alerts

Data Loggers are embedded in every layer from the ground up with the most advanced cyber-security technology, including sensor authentication and data encryption. Receive alerts in case of an urgent event.



## Reduced Cost of Ownership

Low-power and predictive analysis algorithms result in up to 30% extended battery life. Redundant communication concurrently supports LTE (4G), 3G, 2G, LPWAN and Bluetooth connectivity.



## Rapid Deployment & Scalability

The Data Loggers are sensor-agnostic, utilizing various configurations of sensors and samplers. They are easily installed and operating within minutes.

## EcoStruxure IIOT

To transfer all output data, the device is connected to the Schneider Electric Data Logger for a complete remote solution. The Schneider Electric datalogger is an IIoT solution for creating cyber-secure, plug-and-play, affordable smart infrastructure networks.

## Applications

- Water abstraction
- Water production
- Water distribution
- Revenue metering
- Irrigation

# Specifications

Data & Software	
Data Hosting	Secure Cloud or On-Premises
Cyber-Security	TLS 1.2 Protocol
Software Integration	REST API
SCADA Integration	CSV, DNP3 <sup>1</sup> , OPC-UA <sup>1</sup> , FTP <sup>1</sup>
Management Platform	Web-based from desktop, tablet, and mobile
Data Export Options	CSV (Reports)
Device Memory	8 GB
Data Communication	Two-way
Alarm Threshold	Up to 4 per data stream
Alert Notification	SMS, email, voice
System Health Check	Included

Power	
Primary Power Supply	Internal Lithium Battery (field-replaceable and non-rechargeable), 3.9V DC 3A
Internal Battery Capacity	32Ah
Operational Run Time	Up to 5+ years <sup>2</sup>
Battery Status Notifications	Included
External Power	Solar and line power; automatic power source switching
Voltage Input	6-24VDC

Sensor Integration	
Sensor Ports	3 ports; supports up to 12 sensors using cable splitters
Sensor Position	External Hard-Wired
Serial Interfaces	RS485, RS232, SDI-12
Serial Protocols	Modbus RTU, ASCII
Serial Channels	Up to 16
Analog Channels	Up to 4 (4-20 mA, 0-24 V)
Discrete Channels	Dry contact, open collector Up to 5 total inputs (up to 2 pulse counting) 39Hz max pulse frequency Up to 5 outputs, 0V/2.8V Maximum 3 outputs to be used at the same time.
Sensor Power Supply Output	350mA, 3.6V/12V

<sup>1</sup>Minimum Order Quantity (MOQ) - 100 devices.

<sup>2</sup>Battery lifetime depends on sensor power consumption and sampling and transmission frequency.

Connectivity	
Communication	Cellular (4G/3G/2G), LoRaWAN,
Interfaces	Bluetooth
SIM Card(s)	Dual SIM slots
Cellular Roaming	Multi-network global SIM(s); data plan included supporting 180+ countries
Configuration	Remotely (over-the-air)
Upgrades	USB PC connection (internal)
Data Transmission	Periodic, data-dependent
Antenna	External antenna support with backup internal antenna
Built-In GPS	Included

Mechanical Enclosure	
LED Indicator	Included
Dimensions (W x H x D)	13.2 cm x 16.5 cm x 7.3 cm / (5.2 in. x 6.5 in. x 2.9 in.)
Weight	0.9 kg (2.0 lbs)
Enclosure Material	Polycarbonate (UL 94V-0 and UV-resistant)
Ingress Protection	IP 68 / NEMA 6P
Operating Temperature	-40°C to 80°C (-40°F to 176°F)
Storage Temperature	-40°C to 80°C (-40°F to 176°F)

Approvals & Certifications	
Safety	EN 61010-1 2010 / IEC 61010-1
FCC	FCC Part 15 Subpart B, class B
EMC	EN 301 489-1 V2.1.1 2017 / EN 301 489-7 V1.3.1 2005
Spurious Emissions	EN 301 511 V12.5.1 2017
Radiated Emissions	EN 301 908-1 V11.1.1 2016
IP68/NEMA6P	EN 60529:1992+A2:2013 IEC 60529:1989/AM1:1999
CE	Approved

[schneider-electric.com](http://schneider-electric.com)

Life Is On

**Schneider**  
Electric

Schneider Electric  
1602 Mustang Drive  
Maryville, TN 37801  
Email: [supportTRSS@se.com](mailto:supportTRSS@se.com)  
Customer Care  
Toll free: 1.888.226.6876  
Global: 1.613.591.1943